

## E60 ELECTRICAL CONTACT SPRAY

### Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 6/26/2015

Revision date: 2/19/2016

Supersedes: 6/26/2015

Version: 1.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product form : Mixture  
Trade name : E60 ELECTRICAL CONTACT SPRAY  
Product code : E60  
Type of product : Aerosol  
Vaporizer : Aerosol  
Product group : Trade product

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### 1.2.1. Relevant identified uses

Intended for general public

###### 1.2.2. Uses advised against

No additional information available

##### 1.3. Details of the supplier of the safety data sheet

AKKİM YAPI KİMYASALLARI SANAYİ ve TİCARET A.Ş.  
Yeşilbayır mahallesi Şimşir sokak No:22  
34555 İSTANBUL - TURKEY  
T +90 2127711371 - F +90 2127713888  
[info@akfix.com](mailto:info@akfix.com) - [www.akfix.com](http://www.akfix.com)

##### 1.4. Emergency telephone number

Emergency number : +90 2127711371 (9:00 am - 17:00 pm GMT+2)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixture/S

Aerosol, Category 1 H222;H229 On basis of test data

Full text of hazard classes and H-statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause cancer. May cause genetic defects.

##### 2.2. Label elements

###### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

Signal word (CLP) : Danger

Hazardous ingredients : Naphtha (petroleum), hydrotreated heavy, Low boiling point hydrogen treated naphtha, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).]

Hazard statements (CLP) : H222 - Extremely flammable aerosol  
H229 - Pressurised container: May burst if heated

## E60 ELECTRICAL CONTACT SPRAY Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 6/26/2015

Revision date: 2/19/2016

Supersedes: 6/26/2015

Version: 1.0

Precautionary statements (CLP)	: P102 - Keep out of reach of children P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P211 - Do not spray on an open flame or other ignition source P251 - Do not pierce or burn, even after use P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F P260 - Do not breathe spray, vapours P262 - Do not get in eyes, on skin, or on clothing P301+P310 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER P331 - Do NOT induce vomiting
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Naphtha (petroleum), hydrotreated heavy, Low boiling point hydrogen treated naphtha, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] (Note P)	(CAS No) 64742-48-9 (EC no) 265-150-3 (EC index no) 649-327-00-6	50 - 70	Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304
Ethane, 1,1-difluoro-	(CAS No) 75-37-6	30 - 50	Flam. Gas 1, H220 Compressed gas, H280
propan-2-ol, isopropyl alcohol, isopropanol	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0	1 - 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102)-P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

## E60 ELECTRICAL CONTACT SPRAY Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 6/26/2015

Revision date: 2/19/2016

Supersedes: 6/26/2015

Version: 1.0

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurized container: May burst if heated.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

- Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

- Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Recover mechanically the product. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

- For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep cool.

### 7.3. Specific end use(s)

- No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

E60 ELECTRICAL CONTACT SPRAY		
Poland	Local name	Benzyna do lakierów
Poland	NDS (mg/m³)	300 mg/m³
Poland	NDSch (mg/m³)	900 mg/m³
Switzerland	Local name	Naphta* lourd (pétrole), hydro-traité
Switzerland	VME (mg/m³)	300 mg/m³
Switzerland	VME (ppm)	50 ppm
Switzerland	VLE (mg/m³)	600 mg/m³
Switzerland	VLE (ppm)	100 ppm
Switzerland	Remark (CH)	4x15*

## E60 ELECTRICAL CONTACT SPRAY Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 6/26/2015

Revision date: 2/19/2016

Supersedes: 6/26/2015

Version: 1.0

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Wear respiratory protection
Environmental exposure controls	: Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Liquid under pressure.
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 55 - 77 °C
Flash point	: 21 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapour pressure	: > 50 mm Hg
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.802 g/cm <sup>3</sup>
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content	: 55 %
-------------	--------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.



# E60 ELECTRICAL CONTACT SPRAY

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 6/26/2015

Revision date: 2/19/2016

Supersedes: 6/26/2015

Version: 1.0

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity	:	Not classified
-----------------------	---	----------------

Specific target organ toxicity (single exposure)	:	Not classified
--	---	----------------

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

### E60 ELECTRICAL CONTACT SPRAY

Vaporizer	Aerosol
-----------	---------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

### Ethane, 1,1-difluoro- (75-37-6)

LC50 fish 1	733 mg/l
-------------	----------

EC50 Daphnia 1	720 mg/l
----------------	----------

ErC50 (algae)	419 mg/l
---------------	----------

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR) : 1950

UN-No. (IMDG) : 1950

UN-No. (IATA) : 1950

## E60 ELECTRICAL CONTACT SPRAY Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 6/26/2015

Revision date: 2/19/2016

Supersedes: 6/26/2015

Version: 1.0

UN-No. (ADN) : 1950

UN-No. (RID) : 1950

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS  
Proper Shipping Name (IMDG) : AEROSOLS  
Proper Shipping Name (IATA) : Aerosols, flammable  
Proper Shipping Name (ADN) : AEROSOLS  
Proper Shipping Name (RID) : AEROSOLS  
Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D)  
Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1  
Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1  
Transport document description (ADN) : UN 1950 AEROSOLS, 2.1  
Transport document description (RID) : UN 1950 AEROSOLS, 2.1

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 2.1

Danger labels (ADR) : 2.1

:



#### IMDG

Transport hazard class(es) (IMDG) : 2.1

Danger labels (IMDG) : 2.1

:



#### IATA

Transport hazard class(es) (IATA) : 2.1

Hazard labels (IATA) : 2.1

:



#### ADN

Transport hazard class(es) (ADN) : 2.1

Danger labels (ADN) : 2.1

:



#### RID

## E60 ELECTRICAL CONTACT SPRAY Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 6/26/2015

Revision date: 2/19/2016

Supersedes: 6/26/2015

Version: 1.0

Transport hazard class(es) (RID) : 2.1  
Danger labels (RID) : 2.1



#### 14.4. Packing group

Packing group (ADR) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable  
Packing group (ADN) : Not applicable  
Packing group (RID) : Not applicable

#### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

#### 14.6. Special precautions for user

##### - Overland transport

Classification code (ADR) : 5F  
Special provisions (ADR) : 190, 327, 344, 625  
Limited quantities (ADR) : 1I  
Excepted quantities (ADR) : E0  
Packing instructions (ADR) : P207, LP02  
Special packing provisions (ADR) : PP87, RR6, L2  
Mixed packing provisions (ADR) : MP9  
Transport category (ADR) : 2  
Special provisions for carriage - Packages (ADR) : V14  
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12  
Special provisions for carriage - Operation (ADR) : S2  
Tunnel restriction code (ADR) : D

##### - Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959  
Limited quantities (IMDG) : SP277  
Excepted quantities (IMDG) : E0  
Packing instructions (IMDG) : P207, LP02  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D  
EmS-No. (Spillage) : S-U  
Stowage category (IMDG) : None  
Stowage and handling (IMDG) : SW1, SW22  
Segregation (IMDG) : SG69  
MFAG-No : 126

##### - Air transport

PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG



# E60 ELECTRICAL CONTACT SPRAY

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 6/26/2015

Revision date: 2/19/2016

Supersedes: 6/26/2015

Version: 1.0

PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
Special provisions (IATA) : A145, A167, A802  
ERG code (IATA) : 10L

### - Inland waterway transport

Classification code (ADN) : 5F  
Special provisions (ADN) : 190, 327, 344, 625  
Limited quantities (ADN) : 1 L  
Excepted quantities (ADN) : E0  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01, VE04  
Number of blue cones/lights (ADN) : 1

### - Rail transport

Classification code (RID) : 5F  
Special provisions (RID) : 190, 327, 344, 625  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E0  
Packing instructions (RID) : P207, LP02  
Special packing provisions (RID) : PP87, RR6, L2  
Mixed packing provisions (RID) : MP9  
Transport category (RID) : 2  
Special provisions for carriage – Packages (RID) : W14  
Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12  
Colis express (express parcels) (RID) : CE2  
Hazard identification number (RID) : 23

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 55 %

#### 15.1.2. National regulations

##### Germany

VwVwS Annex reference : Water hazard class (WGK) 1, low hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands





# E60 ELECTRICAL CONTACT SPRAY

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 6/26/2015

Revision date: 2/19/2016

Supersedes: 6/26/2015

Version: 1.0

SZW-lijst van kankerverwekkende stoffen	: Naphtha (petroleum), hydrotreated heavy, Low boiling point hydrogen treated naphtha, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] is listed
SZW-lijst van mutagene stoffen	: Naphtha (petroleum), hydrotreated heavy, Low boiling point hydrogen treated naphtha, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F).] is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: None of the components are listed
<b>Denmark</b>	
Class for fire hazard	: Class I-1
Store unit	: 1 liter
Classification remarks	: F <Aerosol 1>; Emergency management guidelines for the storage of flammable liquids must be followed
Recommendations Danish Regulation	: Young people below the age of 18 years are not allowed to use the product The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Compressed gas	Gases under pressure : Compressed gas
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Muta. 1B	Germ cell mutagenicity, Category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H229	Pressurised container: May burst if heated
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer

SDS EU AKFIX

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*